

LUKOIL MOTO 2T SNOW

LUKOIL MOTO 2T SNOW is fully synthetic 2-stroke engine oil specially designed for snow mobiles

APPROVALS

MEETS REQUIREMENTS

API TC
 JASO FD
 ISO-L-EGD
 ISO-L-GD++
 Rotax 253

PRODUCT DESCRIPTION

Because of carefully selected base oils and additives, **LUKOIL MOTO 2T SNOW** has excellent lubrication properties and flow ability even in very cold climate conditions. It reduces exhaust smoke and delivers outstanding protection and cleanliness.

APPLICATION

LUKOIL MOTO 2T SNOW is primarily designed for 2-stroke snow mobiles. It is also suitable for use in other 2-stroke engines which operates under cold climate conditions. Oil is mixed with fuel as engine manufacturer recommends, but it can also be used in oil injection systems.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL MOTO 2T SNOW
Density at 15 °C	kg/m ³	DIN 51575	858
Flash Point COC	°C	ISO 2592	110
Apparent viscosity at -30 °C,	mm ² /s	ASTM D 445	4200
Viscosity at 40°C	mm ² /s	DIN 51562/T1	35
Viscosity at 100°C	mm ² /s	DIN 51562/T1	7,0
Viscosity index	---		166
Pourpoint	°C	DIN ISO 3016	<-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"