

LUKOIL MOTO 4T GARDEN 30

monograde motor oil, for air-cooled and water-cooled 4-stroke engines

APPROVALS

MEETS REQUIREMENTS

API SG, exceed the requirements of all manufacturers of air-cooled and water-cooled 4-stroke low-power motors

PRODUCT DESCRIPTION

LUKOIL MOTO 4T GARDEN 30 is mineral oil-based monograde motor oil developed specifically for the lubrication of air-cooled and water-cooled 4-stroke lawnmowers, small tractors, rotary hoes, tool carriers and other motorised equipment used in gardening and landscape management.

LUKOIL MOTO 4T GARDEN 30 meet the requirements for small, modern four-stroke engines and ensures the highest possible degree of lubrication reliability across wide temperature ranges.

LUKOIL MOTO 4T GARDEN 30 provide excellent thermal load capability, ageing and oxidative stability.

LUKOIL MOTO 4T GARDEN 30 has good cold-starting performance down to -15°C and provide that the entire engine is lubricated quickly. It also guarantees minimal oil consumption due to low evaporation tendency.

APPLICATION

LUKOIL MOTO 4T GARDEN 30 for four-stroke engines in lawnmowers, small tractors, rotary hoes, tool carriers and other motorised equipment used in gardening and landscape management. With its viscosity class of SAE 30 it ensures easy battery or manual starting of tools down to an outside temperature of -15°C.

LUKOIL MOTO 4T GARDEN 30 can also be used to lubricate piston compressors (consult manufacturer's instructions).

LUKOIL MOTO 4T GARDEN 30 can be mixed with other branded oils with no problem; however, it can only perform to its optimum level when unmixed.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL MOTO 4T GARDEN 30
Density/15°C	kg/m ³	DIN 51575	891
Flash point COC	°C	ISO 2592	234
Viscosity class	---	SAE J 300	20W-30
Viscosity/40°C	mm ² /s	DIN 51562/T1	102
Viscosity/100°C	mm ² /s	DIN 51562/T1	11,8
Pour point	°C	DIN ISO 3016	< -27

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Oct. 19, 15, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy +43(1)205 222-8800
 Ölhafen Lobau – Uferstr. 8
 1220 Vienna - Austria www.lukoil-lubricants.eu

member of::

